

# Secvest Wireless Flood Detector

Art. no. FUWM50000

Page 1 of 2



- Suitable for use in the kitchen, bathroom, or basement
- Water-tight sensor
- Reversible (also detects drying, such as for the monitoring of water levels in aquariums)

## Never worry about water damage again

The Secvest wireless flood detector is a technical detector for the Secvest wireless alarm system. It consists of a basic device (detector) and a water sensor connected by a cable. When the sensor comes into contact with water, the detector informs the alarm panel and an alarm is triggered.

## Locations and function

The sensor of the wireless flood detector should be mounted very close to the floor, usually in places that flood first when water damage occurs (such as the tiles behind the washing machine or surfaces near water pipes). If water is detected, an alarm is triggered – even when the alarm system is not armed. Furthermore, you can define whether you are notified by text message or telephone when an alarm is triggered.

## Additional security precautions

It is also possible to connect to the washing machine, in order to switch it off immediately if water is detected.

# Secvest Wireless Flood Detector

Art. no. FUWM50000

Page 2 of 2

## Technical Data:

|                               |                        |
|-------------------------------|------------------------|
| Dimensions                    | (WxHxD) 33x89x29 mm    |
| Battery type                  | 3V CR2 lithium battery |
| Width                         | 33 mm                  |
| Type of detection             | Resistance measurement |
| Radio frequency               | 868,6625 MHz           |
| Transmission power            | 10                     |
| Housing material              | ABS                    |
| Height                        | 89 mm                  |
| Length                        | 29 mm                  |
| Max. battery life             | 2 year(s)              |
| Max. operating temperature    | 50 °C                  |
| Max. sending range (outdoors) | 100 m                  |
| Max. sending range (building) | 30 m                   |

|                            |                |
|----------------------------|----------------|
| Min. operating temperature | -10 °C         |
| Modulation                 | FM FM / AM     |
| Net weight                 | 0.09 kg        |
| Tamper monitoring          | Yes            |
| IP protection class        | 31             |
| Sensor type                | Contact sensor |
| Security level             | 2              |
| Voltage monitoring         | Yes            |
| DC voltage supply          | 3 V            |
| Status display             | Yes            |
| Environmental class        | II             |