

8.4" TFT monitor

Art.-Nr. TVAC10000

Seite 1 von 2



- Full-contrast 8.4" TFT monitor
- SVGA resolution 800 x 600
- Many useful connections: 2 x BNC inputs/outputs, 1 x S-Video, 1 x VGA, 2 x audio
- OSD (on-screen display)
- Integrated loudspeakers
- PIP (picture-in-picture) function with various viewing options

This light, slender LCD monitor has a sturdy design and numerous excellent performance features. The full-contrast 8.4" TFT monitor has two BNC outputs and inputs, an S-Video input as well as one VGA and two audio inputs. Thanks to these connections, the monitor is equipped for a wide range of applications. Two stereo loudspeakers are integrated on the front for direct audio output. This means that this TFT monitor is ideally suited to professional video surveillance.

8.4" TFT monitor

Art.-Nr. TVAC10000

Seite 2 von 2

Technische Daten:

Dimensions	(WxHxD) 210x190x42 mm
Connection type	1xVGA, 1xS-Video, 2x BNC, 2x Audio
Horizontal/vertical viewing angle	150/130 °
Picture format	4:3
Screen diagonal	8.4
Width	210 mm
Display surface	Matte
Color levels	16.2 MIO
Frequency range	31,5-80KHz (H) / 56-75Hz (V) GHz
Functions	PIP
Housing material	Metal frame
Brightness	250 cd/m ²
Height	190 mm
Comb filter	3D
Length	42 mm
Loudspeaker	Integrated, 2x1 W, stereo

Power consumption	11,5 W
Max. operating temperature	40 °C
Max. humidity	85 %
Min. operating temperature	0 °C
Monitor type	Standard TFT LCD
Net weight	1.3 kg
Pixel pitch	0,213 x0,213 (H) x (V) mm
Reaction time	16 ms
Signal detection	Automatic
DC voltage supply	12 V
Power consumption	5000 mA
Video system	PAL / NTSC